

## Range of Fittings for Aluminium Lashing Rails

All aluminium lashing rails have a raster of 25mm. That means you can use any lashing bail, depending on the load requirement.

The lashing rails can be strained with up to 2.500daN (kg), the effective load capacity depends on the lashing bails from 300 to 2.000 daN(kg).

All fittings can be fixed with only one hand and without any tools to any position on the Alu-Lashing rail within seconds.

### Double-Stud Fitting

**Height:** 24.5 mm

**Weight:** 0.11 kg

**Weight Rating:** 1100 daN

**Material:** Zinc plated



### Quattro-Stud Fitting

**Height:** 70 mm

**Weight:** 0.40 kg

**Weight Rating:** 2000 daN

**Material:** Steel



**Height:**

### Automotive Fitting

**Height:** 65 mm

**Weight:** 0.05 kg

**Weight Rating:** 500 daN

**Material:** Zinc plated with plastic retainer



### Heavy Duty Screw Fitting with M10 Nut

**Clamping Range:** 0 – 54 mm

**Weight Rating:** 2000 daN





**M8 Adapter Fitting:**

This adapter can be used for attaching a range of products e.g. Seats, cupboards, storage containers, Motorcycle rails and anything else that requires fixing into place.

Can be used in any lashing rail.

**2x M8 threaded holes for attaching to your application**

**Length:** 100 mm

**Weight:** 0.05 kg

**Weight Rating:** 1000 daN

**Material:** Zinc plated with plastic retainer

