

## H Series Castor Wheels – Heavy Duty

- Up to 550kg load rating per castor
- Zinc plated and 304 grade stainless steel frame options available
- Choice of high temp phenolic and cast iron wheels
- Rigid, swivel and swivel + brake frame options available
- All castors supplied with high-temperature grease
- Plate size 135mm x 110mm
- Hole centres 105 x 80/75 (11)
- Common Uses: Autoclave trolleys, Bakery oven and proving racks, Hospital waste disposal trolleys, Smokehouse trolleys, Powder coating trolley



### EEB

















- » Solid high temperature compression molded epoxy resin
- » Quad Plus Bearings
- » MAX 260°c - Continuous
- » MAX 290°c - Intermittent



### CCP(H)

- » Rugged grey cast iron, machined tread
- » Grease nipple
- » Minimal rolling and swivel resistance
- » Lacquered, colour silver
- » Plain bore
- » Max load reduces to 720kg at 300°C
- » Max load reduces to 520kg at 600°C
- » Bickler wheel code **G150/20G**

## MOUNTING TYPE

WHEEL DIAMETER (mm)	MOUNTING TYPE	FRAME MATERIAL	FRAME CODE	WHEEL ABR	MAX LOAD (KG)	WHEEL ABR	MAX LOAD (KG)	OVERALL HEIGHT (mm)	SWIVEL RADIUS (mm)
100 125 150		ZINC COATED	HZR10050	-EEB	250	-	-	143	-
		ZINC COATED	HZR12550	-EEB	300	-	-	165	-
		ZINC COATED	HZR15050	-EEB	400	-CCP(H)	550	191	-
100 125 150		ZINC COATED	HZS10050	-EEB	250	-	-	143	88
		ZINC COATED	HZS12550	-EEB	300	-	-	165	103
		ZINC COATED	HZS15050	-EEB	400	-CCP(H)	550	191	122
100 125 150		ZINC COATED	HZST10050	-EEB	250	-	-	143	-
		ZINC COATED	HZST12550	-EEB	300	-	-	165	154
		ZINC COATED	HZST15050	-EEB	400	-	-	191	-
100 125 150		<b>STAINLESS</b>	HSR10050	-EEB	250	-	-	143	-
		<b>STAINLESS</b>	HSR12550	-EEB	300	-	-	165	-
		<b>STAINLESS</b>	HSR15050	-EEB	400	-	-	191	-
100 125 150		<b>STAINLESS</b>	HSS10050	-EEB	250	-	-	143	88
		<b>STAINLESS</b>	HSS12550	-EEB	300	-	-	165	103
		<b>STAINLESS</b>	HSS15050	-EEB	400	-	-	191	122
125		<b>STAINLESS</b>	HSSW12550	-EEB	300	-	-	165	103

## WHEELS

WHEEL DIAMETER (mm)	TREAD WIDTH (mm)	WHEEL CODE	MAX LOAD (KG)	BORE DIAMETER (no spacer mm)	BORE DIAMETER (spacer mm)	HUB LENGTH (mm)	TREAD MATERIAL	CENTRE MATERIAL	BEARING TYPE	
100 125 150	50	EE10050B EE12550B EE15050B	250 300 400	1/2" 1/2" 1/2"	- - -	60	HI TEMP EPOXY PHENOLIC		QUAD-PLUS QUAD-PLUS QUAD-PLUS	
150	50	<b>G150/20G*</b>	900	20	-	60			CAST IRON	PLAIN BORE