

## H Series Castor Wheels – Heat Resistant

- Zinc plated and 304 grade stainless steel frame options available
- Choice of high temp phenolic and cast iron wheels
- Rigid, swivel and swivel + brake frame options available
- All castors supplied with high-temperature grease
- **Plate Size:** 135mm x 110mm; Hole centres 105 x 80/75 (11)
- **Common uses:** Autoclave trolleys, Bakery oven & proving racks, Hospital waste disposal trolleys, Smokehouse trolleys, Powder coating trolley



RIGID



SWIVEL



TOTAL LOCKING



WHEEL LOCKING



### EEB













- » Solid high temperature compression molded epoxy resin
- » Quad Plus Bearings
- » MAX 260°C - Continuous
- » MAX 290°C - Intermittent






### CCP(H)

- » Rugged grey cast iron, machined tread
- » Grease nipple
- » Minimal rolling and swivel resistance
- » Lacquered, colour silver
- » Plain bore
- » Max load reduces to 720kg at 300°C
- » Max load reduces to 520kg at 600°C
- » Blicke wheel code **G150/20G**

## MOUNTING TYPE

WHEEL DIAMETER (mm)	MOUNTING TYPE	FRAME MATERIAL	FRAME CODE	WHEEL ABR	MAX LOAD (KG)	WHEEL ABR	MAX LOAD (KG)	OVERALL HEIGHT (mm)	SWIVEL RADIUS (mm)
									
100		ZINC COATED	HZR10050	-EEB	250	-	-	143	-
125		ZINC COATED	HZR12550	-EEB	300	-	-	165	-
150		ZINC COATED	HZR15050	-EEB	400	-CCP(H)	550	191	-
100		ZINC COATED	HZS10050	-EEB	250	-	-	143	88
125		ZINC COATED	HZS12550	-EEB	300	-	-	165	103
150		ZINC COATED	HZS15050	-EEB	400	-CCP(H)	550	191	122
100		ZINC COATED	HZST10050	-EEB	250	-	-	143	
125		ZINC COATED	HZST12550	-EEB	300	-	-	165	154
150		ZINC COATED	HZST15050	-EEB	400	-	-	191	
100		<b>STAINLESS</b>	HSR10050	-EEB	250	-	-	143	-
125		<b>STAINLESS</b>	HSR12550	-EEB	300	-	-	165	-
150		<b>STAINLESS</b>	HSR15050	-EEB	400	-	-	191	-
100		<b>STAINLESS</b>	HSS10050	-EEB	250	-	-	143	88
125		<b>STAINLESS</b>	HSS12550	-EEB	300	-	-	165	103
150		<b>STAINLESS</b>	HSS15050	-EEB	400	-	-	191	122
125		<b>STAINLESS</b>	HSSW12550	-EEB	300	-	-	165	103

## WHEELS

WHEEL DIAMETER (mm)	TREAD WIDTH (mm)	WHEEL CODE	MAX LOAD (KG)	BORE DIAMETER (no spacer mm)	BORE DIAMETER (spacer mm)	HUB LENGTH (mm)	TREAD MATERIAL	CENTRE MATERIAL	BEARING TYPE	AXLE SPACER TYPE
										
100	50	EE10050B	250	1/2"	-	60	HI TEMP EPOXY PHENOLIC		QUAD-PLUS	-
125	50	EE12550B	300	1/2"	-	60			QUAD-PLUS	-
150	50	EE15050B	400	1/2"	-	60			QUAD-PLUS	-
150	50	<b>G150/20G*</b>	900	20	-	60	CAST IRON		PLAIN BORE	