

## EXTRATHANE POLYURETHANE TREAD with CAST IRON CENTRE – Heavy Duty

- Welded steel heavy duty twin wheel castors, strong swivel head design
- Brackets: LSD/BSD series - Particularly rugged welded steel construction, swivel bracket with axial grooved ball bearing DIN 711 and tapered roller bearing DIN 720 in the swivel head, dust and splash-proof, fitted grease nipple, bolted and secured with a welded very strong central kingpin.
- Bolted wheel axle.
- Up to 10,000 kg load rating per castor
- Wheel Ø 80-360 mm: Zinc-plated, yellow-passivated, Cr6-free.
- Wheel Ø 400-500 mm: Lacquered, red.
- GTH series: Made of rugged grey cast iron, wheel Ø 150 mm or larger with grease nipple, lacquered, silver.
- **Bearing type:**  
Two pressed-in ball bearings.
- **NOTE:**  
Fixed castors - long plate is parallel to axle.



## WHEELS

SWIVEL CASTORS	FIXED CASTORS	LOAD CAPACITY (KG)	WHEEL DIAM x WIDTH (mm)	WHEEL BEARING TYPE	OVERALL HEIGHT (mm)	OFFSET SWIVEL CASTOR (mm)	SWIVEL   RIGID PLATE SIZE (mm)	HOLE CENTRES & HOLE SIZE (mm)
LSD-GTH304K	BSD-GTH304K*	5400	300 x 100 ( x 2 )	BALL BEARING	390	80	200 x 255 / 200 x 300	160 x 210(18)
LSD-GTH504K	BSD-GTH504K*	10000	500 x 150 ( x 2 )	BALL BEARING	630	125	300 x 400	240 x 340(26)