

EXTRATHANE POLYURETHANE TREAD with CAST IRON OR ALUMINIUM CENTRE – Heavy Duty



DIE-CAST ALUMINIUM CENTRE

Pressed steel castors, heavy duty brackets, with top plate fitting, wheel with Blicke Extrathane® polyurethane tread

- **Wheels:** ALTH series - Tread: Made of high-quality polyurethane-elastomer Blicke Extrathane®, 92° shore A, light brown, non-marking, non-staining.
- **Wheel centre:** Made of die-cast aluminium.
- **Bearing type:** Two pressed-in ball bearings.

ALUMINIUM CENTRE WHEELS:

SWIVEL CASTORS	FIXED CASTORS	SWIVEL CASTORS WITH BRAKE	MAX LOAD (KG)	WHEEL DIAMETER x WIDTH (mm)	WHEEL BEARING TYPE	OVERALL HEIGHT (mm)	OFFSET SWIVEL CASTOR (mm)	PLATE SIZE (mm)	HOLE CENTRES & HOLE SIZE (mm)
LH-ALTH101K-3	BH-ALTH101K-3	LH-ALTH101K-3-FI	350	100 x 40	BALL BEARING	140	45	140 x 110	105 x 75/80(11)

CAST IRON CENTRE CASTOR:

Pressed steel castors, heavy duty brackets, with top plate fitting, wheel with Blicke Extrathane® polyurethane tread

- **Brackets:** LH/BH series - Made of heavy pressed steel, swivel bracket with heavy fork and top plate, very strong bolted and secured central kingpin, double ball bearing in the swivel head, additionally reinforced by the integration of four specially shaped and hardened bearing seats resulting in a very high resistance to shock and impact loads.
- Bolted wheel axle.
- Zinc-plated, blue-passivated, Cr6-free.
- **Wheels:** GTH series - Tread: Made of high-quality polyurethane-elastomer Blicke Extrathane®, 92° shore A, light brown, non-marking, non-staining.
- **Wheel centre:** Made of rugged grey cast iron, wheel Ø 150 mm or larger with grease nipple, lacquered, silver.
- **Bearing type:** Two pressed-in ball bearings.

CAST IRON CENTRE WHEELS:

SWIVEL CASTORS	FIXED CASTORS	SWIVEL CASTORS WITH BRAKE	MAX LOAD (KG)	WHEEL DIAMETER x WIDTH (mm)	WHEEL BEARING TYPE	OVERALL HEIGHT (mm)	OFFSET SWIVEL CASTOR (mm)	PLATE SIZE (mm)	HOLE CENTRES & HOLE SIZE (mm)
LH-GTH125K-3	BH-GTH125K-3	LH-GTH125K-3-FI	500	125 x 40	BALL BEARING	165	45	140 x 110	105 x 75/80(11)
LH-GTH150K	BH-GTH150K	LH-GTH150K-FI	750	150 x 50	BALL BEARING	197	65	140 x 110	105 x 75/80(11)
LH-GTH200K	BH-GTH200K	LH-GTH200K-FI	900	200 x 50	BALL BEARING	245	70	140 x 110	105 x 75/80(11)