

## EXTRATHANE POLYURETHANE TREAD with CAST IRON CENTRE – Heavy Duty

- **Welded steel heavy duty castors, strong swivel head design.**
- **Brackets:** LS/BS series - Particularly rugged welded steel construction, swivel bracket with axial grooved ball bearing DIN 711 and tapered roller bearing DIN 720 in the swivel head, dust and splash-proof, fitted grease nipple, bolted and secured with a welded very strong central kingpin.
- Bolted wheel axle.
- Wheel Ø 125-400 mm: Zinc-plated, yellow-passivated, Cr6-free.
- Wheel Ø 500-600 mm: Lacquered, red.
- **Wheels:** GTH series - Tread: Made of high-quality polyurethane-elastomer Blicke Extrathane®, 92° shore A, light brown, non-marking, non-staining.
- **Wheel centre:** Made of rugged grey cast iron, wheel Ø 150 mm or larger with grease nipple, lacquered, silver.
- **Load Rating:** Up to 5,000 kg
- **Bearing type:** Two pressed-in ball bearings.



## WHEELS

SWIVEL CASTORS	FIXED CASTORS	SWIVEL CASTOR WITH BRAKE	SWIVEL CASTOR WITH WHEEL BRAKE	SWIVEL CASTORS WITH 2 OR 4 WAY DIRECTIONAL LOCK	MAX LOAD (KG)	WHEEL DIAMETER x WIDTH (mm)	OVERALL HEIGHT (mm)	OFFSET SWIVEL CASTOR (mm)	PLATE SIZE (mm)	HOLE CENTRES & HOLE SIZE (mm)
LS-GTH202K	BS-GTH202K	LS-GTH202K-ST		LS-GTH202K-RI2	1600	200 x 80	255	65	175 x 140	140 x 105(14)
LS-GTH252K	BS-GTH252K	LS-GTH252K-ST		LS-GTH252K-RI2	1800	250 x 80	305	75	175 x 140	140 x 105(14)
LS-GTH302K	BS-GTH302K	LS-GTH302K-ST		LS-GTH302K-RI2	2400	300 x 80	355	85	175 x 140	140 x 105(14)
LS-GTH304K	BS-GTH304K		LS-GTH304K-RAH		3000	300 x 100	370	85	200 x 160	160 x 120(14)
LS-GTH364K	BS-GTH364K		LS-GTH364K-RAH		3800	360 x 120	430	100	255 x 200	210 x 160(18)
LS-GTH406K	BS-GTH406K				5000	400 x 125	480	125	255 x 200	210 x 160(18)